



Can be diluted with water.



It must be diluted according to

the porosity of the substrate to be treated, however with no addition of water in a quantity over 6 times the product.



The product covers 12±15 m²/lt according to the absorption of the substrate.



In normal temperature conditions (22°C) and relative humidity (60%), the surface is dry to the touch in 4÷6 hours and can be painted over after 12÷18 hours.



Use at ambient temperatures between 10°C and 30°C. Avoid

application in case of strong rain, wind and high sunlight.



Store the product at a temperature, no lower than 5°C out of direct

sunlight. The product, stored and sealed in the original packages, keeps for a period of 2 (two) years.



Store the product at a temperature, no lower than 5°C out of direct sunlight. The

product, stored and sealed in the original packages, keeps for a period of 2 (two) years.



Modern substrate product to even out the absorption capacity of the walls (particularly interior) to be treated with breathable or washable paint, avoiding the formation of marks and streaks.

Acrylic sealing fixative for interiors and exteriors.

CICLO: New interior walls: clean the surface well, make sure it is perfectly dry, fill any cracks and/or small holes with "MASTICFAS" or with "STUCCO IN PASTA". After around 1÷2 hours apply Fissativo isolante all'acqua, in the dilution required by the substrate absorption capacity.

Interior walls that are already painted: accurately clean the wall, removing any old flaky paint by scraping. If there is mould, treat the walls with "RISANMUR". Fill any imperfections and/or holes with "MASTICFAS" or with "STUCCO IN PASTA". After apply Fissativo isolante all'acqua in the dilution required by the substrate absorption capacity.

Exterior walls: proceed by following indications for interior surfaces, but use "STUCCO PER ESTERNO" for filling.

Rev.: 4.0 - 14/12/2021

VOLATILE ORGANIC COMPOUNDS
EU limit value VOC
(Directive 2004/42 EC)
Binding primers
(Cat A/h) BA 30 gr/lt (2013)
FISSATIVO ISOLANTE ALL'ACQUA
max contains 30 gr/lt VOC

Specific gravity: 1,050 kg/l





8012760941464 750 ml

8012760941457 4000 ml

| FORMATS AVAILABLE | DIMENSIONS P x L x H (mm) | PCS. X IMB. | LAYERS P. | X LAYER | X PALLET |
|-------------------|---------------------------|-------------|-----------|---------|----------|
| 750 ml | 83x83x240 | 6 | 4 | 90 | 360 |
| 4000 ml | 190x135x245 | 1 | 4 | 30 | 120 |

WARNINGS: Mix the product well before use.

NOTE: Ideal environmental conditions: temperature: min. +8°C - max +35°C relative humidity<75%.

Ideal substrate conditions: temperature: min. +5°C - max +35°C - humidity<10%.

It is recommended to apply the product in favourable climatic conditions as indicated.

Keep the product out of the reach of children.

in favourable climatic conditions as indicated. Applying the product in unsuitable environmental conditions, negatively affects the drying time, compromising the optimal result of both the aesthetic characteristics and its performance.

Do not apply on fresh and alkaline substrates; wait for it to cure (generally four weeks).

Use in a well-ventilated area.

CIPIR ensures that the information is provided to the best of its experience and technical-scientific knowledge; nevertheless, it cannot assume any responsibility for the results obtained as application conditions are beyond its control.