



Ready to use.



Can be used with the sprayer provided with the package.



Use at ambient temperatures between 10°C and 30°C.



Store the product at a temperature, no lower than 5°C out of direct sunlight. The product, stored and sealed in the original packages, keeps for a period of 2 (two) years.



Store the product at a temperature, no lower than 5°C out of direct sunlight. The product, stored and sealed in the original packages, keeps for a period of 2 (two) years.



*Suitable for the hygienic and environmental recovery of bathrooms, kitchens, basements and other particularly damp rooms or for external walls and products.*

**Instant destroyer of mould, algae and moss.**

**CICLO:** After thoroughly cleaning the surface to be treated, spray Pulitore macchie e muffe bagno at a distance of 3-5 cm and then repeat after 10 minutes if the stains persist, then wash the surface with water. Pulitore macchie e muffe bagno is particularly indicated for using on flooring joints, corners of particularly damp rooms such as bathrooms, showers, saunas, basements and garages, as well as interior and exterior manufactured products such as swimming pools, balconies, planters and so on.

Rev.: 4.0 - 14/12/2021





8007887950925 500 ml

FORMATS AVAILABLE	DIMENSIONS P x L x H (mm)	PCS. X IMB.	LAYERS P.	X LAYER	X PALLET
500 ml	83x83x230	6	4	90	360

**WARNINGS:** It is irritating for the respiratory system, so it must be handles safely and be kept out of the reach of children. Do not use together with other chemical products. Carefully reclose the container after use.

**NOTE:** Condizioni ideali dell'ambiente: temperatura: min. +8°C ÷ max +35°C - umidità relativa <75%.

Condizioni ideali del supporto: temperatura: min. +5°C ÷ max +35°C - umidità <10%.

Si raccomanda di applicare il prodotto in condizioni climatiche favorevoli come indicato.

Conservare il prodotto fuori dalla portata dei bambini.

L'applicazione del prodotto eseguita in condizioni atmosferiche non idonee influenza negativamente i tempi di essiccazione compromettendo il raggiungimento delle caratteristiche estetiche e prestazionali.

Non applicare su supporti freschi e tendenzialmente alcalini, attendere un tempo adeguato di maturazione. (generalmente di quattro settimane).

Usare in luogo ben ventilato.

CIPIR garantisce che le informazioni sono fornite al meglio della sua esperienza e conoscenza tecnico-scientifica; tuttavia non può assumere alcuna responsabilità per i risultati ottenuti in quanto le condizioni di applicazione sono al di fuori di ogni suo controllo.